














3M™ Filtering Facepiece Respirators*

3M™ Filtering Facepiece Respirators

| | | |
|-----------------|---|---|
| 1860 |  | 3M™ Health Care Particulate Respirator and Surgical Mask 1860. Minimum 95% filter efficiency. (NIOSH N95 approved). Features a soft inner shell for enhanced comfort. Reduces potential exposure to blood and other body fluids. Meets CDC guidelines for TB exposure control. Not for use in atmospheres containing oil aerosols. |
| 1865 |  | 3M™ Health Care Particulate Respirator and Surgical Mask 1860S. Designed for people with smaller faces. Minimum 95% filter efficiency. (NIOSH N95 approved). Features a soft inner shell for enhanced comfort. Reduces potential exposure to blood and other body fluids. Meets CDC guidelines for TB exposure control. Not for use in atmospheres containing oil aerosols. |
| 8000 |  | 3M™ Particle Respirator 8000, N95. Minimum 95% filter efficiency. This is an economical product that is designed for light-duty or short duration work in dusty environments. Features adjustable noseclip. Not for use in atmospheres containing oil aerosols. |
| 8110S |  | 3M™ Particulate Respirator 8110S, N95. Designed for people with smaller faces. Minimum 95% filter efficiency. Features adjustable noseclip and soft nose foam pad that help provide a custom fit and secure seal. Not for use in atmospheres containing oil aerosols. |
| 8200 |  | 3M™ Particulate Respirator 8210, N95. Minimum 95% filter efficiency. Features adjustable noseclip and soft nose foam pad that help provide a custom fit and secure seal. Not for use in atmospheres containing oil aerosols. |
| 8200PLUS |  | 3M™ Particulate Respirator 8210Plus, N95. Minimum 95% filter efficiency. Comfortable braided straps with staple-free attachment. Not for use in atmospheres containing oil aerosols. |
| 8233 |  | 3M™ Particulate Respirator 8233, N100. Minimum 99.97% filter efficiency. Features adjustable straps, 3M™ Cool Flow™ Exhalation Valve for cool and dry comfort, and face seal. Not for use in atmospheres containing oil aerosols. |
| 8271 |  | 3M™ Particulate Respirator 8271, P95. Minimum 95% filter efficiency. Features M-noseclip, 3M™ Cool Flow™ Exhalation Valve for cool and dry comfort, and face seal. |
| 8293 |  | 3M™ Particulate Respirator 8293, P100. Minimum 99.97% filter efficiency. Features adjustable straps, 3M™ Cool Flow™ Exhalation Valve for cool and dry comfort, and face seal. |
| 8511 |  | 3M™ Particulate Respirator 8511, N95. Minimum 95% filter efficiency. Features M-noseclip, 3M™ Cool Flow™ Exhalation Valve for cool and dry comfort, and face seal. Not for use in atmospheres containing oil aerosols. |
| 8577 |  | 3M™ Particulate Respirator 8577, P95. Minimum 95% filter efficiency. 3M recommended for relief against nuisance level organic vapor.** Features 3M™ Cool Flow™ Exhalation Valve for cool and dry comfort. |
| 9210 |  | 3M™ Particulate Respirator 9210, N95. Minimum 95% filter efficiency. Features unique 3-panel design, soft nose foam pad and advanced electret media. Conforms to a wide range of faces. Folds flat for easy storage and portability. Individually packaged. Not for use in atmospheres containing oil aerosols. |
| 9211 |  | 3M™ Particulate Respirator 9211, N95. Minimum 95% filter efficiency. Features unique 3-panel design, soft nose foam pad, advanced electret media and 3M™ Cool Flow™ Exhalation Valve. Conforms to a wide range of faces. Folds flat for easy storage and portability. Individually packaged. Not for use in atmospheres containing oil aerosols. |



3M™ Half Facepiece
6100, 6200, 6300



3M™ Half Facepiece
6100DD, 6200DD, 6300DD



3M™ Particulate
2091, P100



3M™ Particulate
2097, P100* **
with Nuisance Level
Organic Vapor Relief



3M™ Particulate
7093, P100

*3M recommended for ozone protection up to 10 x OSHA PEL.

This product is not NIOSH approved for ozone protection.

**Nuisance level refers to concentrations below the current OSHA PELs

FIT TEST KIT

3M equipment and procedures provide a simple, direct way to meet OSHA qualitative fit testing requirements. These products can be used with any particulate or gas/vapor respirator with a particulate filter to test face-to-respirator seal. The equipment helps satisfy respiratory program requirements, and is easy to use during respiratory training.



FT-10



3M™ Qualitative Fit Test
Apparatus FT-10, Sweet

FT-30



3M™ Qualitative Fit Test
Apparatus FT-30, Bitter